



Modern Hydraulic Technology

division of Newark Special Technology, Inc.

1250 ton SOUTHWARK [Stock Number 898]

Construction	4 Posts, 11-1/2" Dia. Each
Stroke	48"
Daylight Opening	72"
Bed & Slide Working Area	12' L-R x 11' F-B or 8' L-R x 16' F-B
Distance Between Posts	12' L-R x 8' F-B
Bed & Slide Overall	16' L-R x 11' F-B, "T" Slotted
Slide	Fully Guided
Main Rams	(3) 26" Dia. Each @ 1500 PSI
Press Can Be Run In Increments of 580 tons	1, 2 or 3 Rams
Push Ups (4)	7" Dia. Each, Total lifting tonnage 115 @ 1500 PSI
All Mounted in 4 Corners of the Bed.	
Knockouts	(3), 40 tons each
(1) center of bed	36" stroke
(2) end of bed, adjustable 24" on long axis of bed, 24" stroke each	
Mounted on Press Crown	Prefill Tank, (1) 5" Prefill Valve

Manually Operated Lever Control Valves Replaced w/Electrical Controls 1965.

All Operator Controls Mounted in a Pendant with the following: Selector Switch for tonnage Changes, Rapid Advance "Down" for any Press Cap., Pressure Advance "Down", Rapid "Up" Travel of Platen, Ejector "Up", Ejector "Retract".

Overall Length	Above Floor 23'9-1/2", Below Floor 6'6" x 18' L-R x 11' F-B
Total Weight	412,000 Lbs. Approx.

Press was operated from a central hydraulic pumping system. As such, no pumping system is included. We can supply a new one to customer's requirements at additional cost.

F.O.B., trucks, Lester, PA



Visit our website at www.modernhydraulic.com