



MODERN HYDRAULIC TECHNOLOGY

DIVISION OF NEWARK SPECIAL TECHNOLOGY, INC.

750 ton UNIVAN [Stock Number 1737]

Construction 4 posts, 7-1/2" diameter each
Stroke 10" (approximate)
Daylight opening 21-1/2"

Bed working area
65-1/2" F-B x 25" L-R (side loading)
29" L-R x 25" F-B (front loading)

Distance between posts 29" L-R x 29" F-B
Slide fully guided
Ram diameter 28"
Pullbacks (2)
Prefill valve 4"

Hydraulics

Mounted on press crown, 60 HP motor 230/450/3/60, 1175 RPM,
150/75 amp; driving a Vickers pump PVE45-FRSF-21-RAA-11.

Estimated speeds: 75 IPM approach; 10 IPM pressing; 100 IPM
opening.

Controls Electric push button.

Pit or platform required

Approximate overall dimensions 15'7" high x 6'5" x 4'8"

Approximate weight 54,000 lbs.

F.C.A. LOADED Philadelphia, Pa



Phone (215) 467 9000 • Fax (215) 467 9220
1900 Kittyhawk Ave., Building 57 Bay – A, Philadelphia, PA 19112, USA
Visit our website at www.hydraulicpresses.com